

## Series 1800 Polyurethane Lined Abrasion Resistant PVC Material Handling Hose (Dry Application)



For conveying of solids where abrasive conditions are present. Specially formulated, static-dissipating HMV PVC compound provides sub-zero flexibility. The smooth polyurethane lining eliminates material build up.

<b>Tube:</b>	Polyurethane Lined (static dissipating)
<b>Reinforcement:</b>	High density rigid PVC helix
<b>Cover:</b>	Black HMV PVC - Convuluted
<b>Temperature:</b>	-40°F to +150°F (-40°C to +65°C)

Part #	I.D. (In)	O.D. (In)	Approx. Liner Thickness (mm)	Vacuum Rating (In Hg) @ 70°F	W.P. @ 70°F (PSI)	Bend Radius @ 70°F (In)	Weight (Lbs / Ft)	Std. Length	Stock (Yes) or Min. Order
1800-150	1-1/2	1.86	.6	29	50	2.0	.42	100'	Yes
1800-200	2	2.40	.7	29	40	2.0	.59	100'	Yes
1800-250	2-1/2	3.07	.9	29	40	4.0	.80	100'	1000'
1800-300	3	3.65	1.0	29	40	4.0	1.18	100'	Yes
1800-400	4	4.77	1.2	29	35	6.0	1.95	100'	Yes
1800-600	6	6.83	1.5	28	30	12.0	3.50	50'/100'	Yes
1800-800	8	9.18	2.0	28	30	18.0	5.91	20'/50'	200'